

SECTION
Scale: 1/2" = 1'-0"



DETAIL 'A'
Scale: 1/2" = 1'-0"

Notes:
1. Existing structure shown in dashed lines.
2. This detail is only required where A dimension is 2'-6" or greater.
3. This detail can be used for maximum stringer spacing of 10' and maximum diaphragm spacing of 25'.
4. All structural steel to be ASTM A 709 Grade 36 or better.
5. All bolts to be 7/8" ϕ ASTM A-325 and holes to be 15/16" ϕ.
6. Member sizes and connections shown are minimums. Engineer shall design.

APPROVAL
E.S. Freedman DIRECTOR OFFICE OF BRIDGE DEVEL.
DATE: 9/2/83

REVISIONS	
SHA	FHWA
9-24-96	·
1-22-01	·
10-22-03	·
10-9-07	·

FHWA APPROVAL
DATE: 10-7-83

STATE OF MARYLAND
DEPARTMENT OF TRANSPORTATION
STATE HIGHWAY ADMINISTRATION
OFFICE OF BRIDGE DEVELOPMENT

DETAIL OF TEMPORARY SLAB UNDERPINNING DURING STAGE CONSTRUCTION

STANDARD NO. M(8.01)-83-153 SHEET 1 OF 1

MISCELLANEOUS